



UNIVERSAL. CONSTANT. EXACT.

PRECISION TINED WEEDER AEROSTAR-EXACT

With the precision tined weeder AEROSTAR-EXACT, row crops such as corn, soya, sunflower, field bean, pumpkin as well as seeds or vegetables can be weeded at the cotyledon stage. But also precise blind weeding is possible with the AEROSTAR-EXACT - thanks to the exact depth control and above all the exact adjustment possibilities of the tine aggressiveness.

The AEROSTAR-EXACT is the professional version of the classic AEROSTAR tined weeder. Many of the AEROSTAR's options are already integrated in the standard equipment of the precision tined weeder AEROSTAR-EXACT.



Precise (blind) weeding of corn, beets, pumpkins, soybeans, potatoes, wheat, rye, field beans, peas, etc.



Type/ Working width cm / ft	Sections m / ft	Wheels	Tines	from hp/kW	Weight approx. kg / lbs
RIGID, not foldable					
AEROSTAR-EXACT 300 / 9.8	2x1.5 / 2x4.9	4	120	40/29	540 kg 1190 lbs
Hydraulic folding					
AEROSTAR-EXACT 600 / 19.7	4x1.5 / 4x4.9	6	240	70/51	940 kg 2072 lbs
AEROSTAR-EXACT 750 / 24.6	5x1.5 / 5x4.9	6	300	80/59	1200 kg 2646 lbs
AEROSTAR-EXACT 900 / 29.5 ¹⁾	6x1.5 / 6x4.9	6	360	90/66	1600 kg 3527 lbs
AEROSTAR-EXACT 1200 / 39.4 ¹⁾	8x1.5 / 8x4.9	6	480	100/74	1880 kg 4145 lbs
AEROSTAR-EXACT 1500 / 49.2 ^{1,2)}	10x1.5 / 10x4.9	6	600	150/110	2280 kg 5027 lbs
AEROSTAR-EXACT 1800 / 59.1 ^{1,2,3)}	12x1.5 / 12x4.9	10	720	200/147	3220 kg 7099 lbs

1) Shear retraction + hydr. transport lock

2) Transport height approx. 4,5 m (14.8 ft)

3) Transport width 6 m (19.7 ft)

STANDARD EQUIPMENT

- ✓ Tines ø 7 mm / 0.28", 600 mm / 20.87" long | individually exchangeable | 10 cm wear length
- ✓ Real line spacing 2.5 cm / 1"
- ✓ Sturdy, durable plastic tine holder
- ✓ Tube frame section providing equal working pressure over the full section width
- ✓ 6 row tine section and 1.5 m wide
- ✓ Hydraulic tine adjustment per section with position indicator
- ✓ Sections fixed at the front and rear
- ✓ Lower links with quick coupling pendular axle (up to model 600)
- ✓ Sturdy tube frame | adjustable rubber support wheels | parking support for hydr. foldable machines
- ✓ The side sections swing in automatically through parallel guidance (for hydr. foldable machines)
- ✓ Upper link with slotted hole for ideal operation in hilly fields
- ✓ Pendular chassis on the back of machine
- ✓ Rear support wheels with trailed weeder tines
- ✓ Large, bearing mounted rubber support wheels with tractor tyre tread
- ✓ From model 900 with hydraulic transport lock

OPTIONS

- » Tine holder for row crops
- » Weeder extension 30 cm / 11.8"
- » Twin wheels on the track
- » Electrical control valve
- » Pneumatic seeding box P-BOX-STI up to 12 m / 40ft
- » Warning signs with holder and LED-light