



LIQUID. COMBINABLE. EFFICIENT.

FRONT TANK FOR LIQUIDS JUMBO-STREAM

The JUMBO-STREAM front tank for liquids offers efficient solutions for combined weed management. The new front tank enables efficient mechanical weed control in combination with the proven CHOPSTAR hoeing equipment, i.e. hoeing and band spraying in one operation.

The camera-controlled ROW-GUARD does not only allow for a precise guidance of hoeing elements between rows, but also the nozzles are accurately guided above the row of plants to be treated. As a result, most of the weed control is done with the row-crop cultivator and only a very small area is treated chemically. These tailor-made solutions for liquid application can thus be used to efficiently combine work sequences, reduce application amounts and consequently increase the effectiveness of weed control. Efficient fertilization can be successfully done with the JUMBO-STREAM. Fertilizer can be brought directly to the plant supplying the crop with the appropriate nutrients when combined with a CHOPSTAR row-crop cultivator.



Model	JUMBO-STREAM 1100
Tank capacity (l)	1100
Tare weight	220 kg / 485 lbs
Handling	Electronic (ISOBUS)
Clean water tank (l)	2x65
Front linkage	Kat. II
Pump capacity (l/min)	200
Level indicator	Electronic

STANDARD EQUIPMENT

- ✓ Front tank 1100 litres tank capacity (max. 1300 litres) | Mounting category II
- ✓ Hydr. driven piston-diaphragm pump
- ✓ Electric control via ISOBUS (Front-Isobus plug, ISOBUS-cabeling, ISOBUS-monitor, as well as SECTION-control need to be available from the tractor)
- ✓ Electrical fluid-level indicator
- ✓ 2 x 65 l clean water tank for cleaning of tank and pumps, with rotation nozzle for internal cleaning of the tank, hand wash tank
- ✓ Entire filter system (filling strainer, intake filter, pressure filter, nozzle filter)
- ✓ Parking wheels for easy movement
- ✓ Control units and nozzles are mounted to the rear implement
- ✓ Intake connection Camlock 2
- ✓ Flow rate meter for distribution rate up to 20 l/min
- ✓ Front lights
- ✓ ATTENTION: If a technical inspection is required by the legislator of the country of use, it has to be undertaken on site

OPTIONS

- » Section-Control activation
- » Mounting kits for the row-crop cultivator 6, 8, 12, 16 or 18-row
- » Flow meter for high application rates (2.5 - 50 l/min)



State-of-the-art technology for front and rear implements thus guaranteeing savings and efficient hoeing as well as simultaneous band spraying!